

**Description**

Hole Diameter: 29/64", Diameter: 49/64", Thickness: 1/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1252716LC
Minimum Qty (MOQ):	1000 EA
NSN:	5310-01-501-2158
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE  
AVAILABLE

## P/N NAS1252-716LC Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.443 Inches Minimum And 0.463 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.032 Inches Nominal
<b>Overall Diameter:</b>	0.745 Inches Minimum And 0.770 Inches Maximum
<b>End Item Identification:</b>	Hydraulic Installation Ldg Gear Misc Sec Pwr Misc
<b>Part Name Assigned By Controlling Agency:</b>	Washer- 7075 Aluminum Alloy Flat
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Qq-a-250/12 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Type II, Class 2 (yellow) Mil Spec Single Treatment Response Overall

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-716LC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.