

**Description**

size: #8, thickness 0.063", 7075-t6 aluminum alloy, NAS1252 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS12528H
Minimum Qty (MOQ):	100
NSN:	5310-01-499-9243
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N NAS1252-8H Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.164 Inches Minimum And 0.184 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.057 Inches Minimum And 0.069 Inches Maximum
<b>Overall Diameter:</b>	0.370 Inches Minimum And 0.395 Inches Maximum
<b>End Item Identification:</b>	Used On C-17a Aircraft
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-250/12 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Type II, Class 2 (yellow) Mil Spec Single Treatment Response Overall

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-8H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.