

Description

size: #8, thickness 0.063", 7075-t6 aluminum alloy, NAS1252 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12528H
Minimum Qty (MOQ):	100
NSN:	5310-01-499-9243
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS1252-8H Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.164 Inches Minimum And 0.184 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Overall Diameter:	0.370 Inches Minimum And 0.395 Inches Maximum
End Item Identification:	Used On C-17a Aircraft
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type II, Class 2 (yellow) Mil Spec Single Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-8H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.