

P/N NAS1252-8L

Description

size: #8, thickness 0.032", aluminum alloy

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS12528L

Minimum Qty (MOQ): 100

NSN: 5310-00-410-4362

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









P/N NAS1252-8L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.164 Inches Minimum And 0.184 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.370 Inches Minimum And 0.395 Inches Maximum
Heat Treatment:	F-as Fabricated
Material:	Aluminum Alloy 7075 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/NAS1252-8L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.