

**Description**

size: #8, thickness 0.032", aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS12528L
Minimum Qty (MOQ):	100
NSN:	5310-00-410-4362
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



## P/N NAS1252-8L Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.164 Inches Minimum And 0.184 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Center Hole Shape Style:</b>	Round
<b>Thickness:</b>	0.028 Inches Minimum And 0.036 Inches Maximum
<b>Overall Diameter:</b>	0.370 Inches Minimum And 0.395 Inches Maximum
<b>Heat Treatment:</b>	F-as Fabricated
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-8L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.