

Description

size: #8, thickness 0.032", aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS12528L
Minimum Qty (MOQ):	100
NSN:	5310-00-410-4362
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N NAS1252-8L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.164 Inches Minimum And 0.184 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.370 Inches Minimum And 0.395 Inches Maximum
Heat Treatment:	F-as Fabricated
Material:	Aluminum Alloy 7075 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-8L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.