

Description

size: #8, thickness 0.032", aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS12528L |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-00-410-4362 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



P/N NAS1252-8L Specifications

| | |
|---|---|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.164 Inches Minimum And 0.184 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Center Hole Shape Style: | Round |
| Thickness: | 0.028 Inches Minimum And 0.036 Inches Maximum |
| Overall Diameter: | 0.370 Inches Minimum And 0.395 Inches Maximum |
| Heat Treatment: | F-as Fabricated |
| Material: | Aluminum Alloy 7075 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-8L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.