

Description


Hole Diameter: 37/64", Diameter: 1-5/64", Thickness: 1/16", NAS1252 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1252916H
Minimum Qty (MOQ):	100
NSN:	5310-01-128-6058
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N NAS1252-916H Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.568 Inches Minimum And 0.588 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Overall Diameter:	1.057 Inches Minimum And 1.082 Inches Maximum
Color:	Yellow Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1252 Professional/Industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-916H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.