

Description

12 point, drilled

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS12714 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-481-6509 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1271-4 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.460 Inches Minimum And 0.510 Inches Maximum |
| Fastener Length: | 0.720 Inches Minimum And 0.750 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.290 Inches Minimum And 0.310 Inches Maximum |
| Width Between Flats: | 0.306 Inches Minimum And 0.315 Inches Maximum |
| Extended Washer Diameter: | 0.428 Inches Minimum And 0.438 Inches Maximum |
| Extended Washer Thickness: | 0.059 Inches Minimum And 0.079 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Titanium Alloy Uns R54520 Overall |
| Material Document And Classification: | Nas621,comp 6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1271 Professional/Industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1271-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.