

P/N NAS1271-5

Description

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS12715
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-573-2774
Schedule B:	8108.90.3060
FCCN:	0Δ001



^{*} See page 2 for technical characteristics

P/N NAS1271-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.485 Inches Nominal
Fastener Length:	0.860 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.290 Inches Minimum And 0.310 Inches Maximum
Width Between Flats:	0.306 Inches Minimum And 0.315 Inches Maximum
Extended Washer Diameter:	0.360 Inches Nominal
Extended Washer Thickness:	0.059 Inches Minimum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.375 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Surface Finish:	16.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	As-4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1271 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1271-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.