

Description

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS12715 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-573-2774 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS1271-5 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.485 Inches Nominal |
| Fastener Length: | 0.860 Inches Nominal |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.290 Inches Minimum And 0.310 Inches Maximum |
| Width Between Flats: | 0.306 Inches Minimum And 0.315 Inches Maximum |
| Extended Washer Diameter: | 0.360 Inches Nominal |
| Extended Washer Thickness: | 0.059 Inches Minimum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.375 Inches Nominal |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Surface Finish: | 16.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | As-4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1271 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1271-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.