

**Description**

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS12716
Minimum Qty (MOQ):	5
NSN:	5306-01-572-7881
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1271-6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.460 Inches Minimum And 0.510 Inches Maximum
<b>Fastener Length:</b>	0.860 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.290 Inches Minimum And 0.310 Inches Maximum
<b>Width Between Flats:</b>	0.306 Inches Minimum And 0.315 Inches Maximum
<b>Extended Washer Diameter:</b>	0.428 Inches Minimum And 0.438 Inches Maximum
<b>Extended Washer Thickness:</b>	0.059 Inches Minimum And 0.079 Inches Maximum
<b>Grip Diameter:</b>	0.248 Inches Minimum And 0.249 Inches Maximum
<b>End Item Identification:</b>	Nimrod 2000
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.375 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Titanium Alloy Uns R54520 Overall
<b>Material Document And Classification:</b>	Anas621.comp 6al-4v Assn Std All Material Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1271-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.