

Description

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12716
Minimum Qty (MOQ):	5
NSN:	5306-01-572-7881
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1271-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.460 Inches Minimum And 0.510 Inches Maximum
Fastener Length:	0.860 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.290 Inches Minimum And 0.310 Inches Maximum
Width Between Flats:	0.306 Inches Minimum And 0.315 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.438 Inches Maximum
Extended Washer Thickness:	0.059 Inches Minimum And 0.079 Inches Maximum
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
End Item Identification:	Nimrod 2000
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.375 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Titanium Alloy Uns R54520 Overall
Material Document And Classification:	Anas621.comp 6al-4v Assn Std All Material Responses Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1271-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.