

Description

Fastener Length: 53/64", Hole Diameter: ", Thread: 1/4-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1272H4 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-130-7655 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR 99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1272H4 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.547 Inches Minimum And 0.597 Inches Maximum |
| Fastener Length: | 0.807 Inches Minimum And 0.837 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.338 Inches Minimum And 0.358 Inches Maximum |
| Width Between Flats: | 0.368 Inches Minimum And 0.377 Inches Maximum |
| Extended Washer Diameter: | 0.521 Inches Minimum And 0.531 Inches Maximum |
| Extended Washer Thickness: | 0.072 Inches Minimum And 0.092 Inches Maximum |
| Hole Diameter: | 0.055 Inches Nominal |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Round |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Nas 621 Comp 6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1272H4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.