

**Description**

Thread: 2-56, Thread Size: 1/8", Head Width: 1/8", locknut, dry film, NAS1291 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[PLH502M](#)

SKU / Model:	NAS1291C02M
Minimum Qty (MOQ):	20
NSN:	5310-00-813-6950
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1291C02M Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Washer Outside Diameter:</b>	0.169 Inches Maximum
<b>Overall Height:</b>	0.080 Inches Minimum And 0.100 Inches Maximum
<b>Nut Style:</b>	Hexagon
<b>Washer Thickness:</b>	0.035 Inches Minimum
<b>Width Across Flats:</b>	0.122 Inches Minimum And 0.127 Inches Maximum
<b>Temp Rating:</b>	550.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	56
<b>Nominal Thread Size:</b>	0.086 Inches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this self-locking extended washer nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+extended+washer+nuts/NAS1291C02M](https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1291C02M) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.