

## **P/N NAS1291C02M**

## **Description**

Thread: 2-56, Thread Size: 1/8", Head Width: 1/8", locknut, dry film, NAS1291 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### PLH502M

SKU / Model: NAS1291C02M


Minimum Qty (MOQ): 20

NSN: 5310-00-813-6950


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1291C02M Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.169 Inches Maximum
Overall Height:	0.080 Inches Minimum And 0.100 Inches Maximum
Nut Style:	Hexagon
Washer Thickness:	0.035 Inches Minimum
Width Across Flats:	0.122 Inches Minimum And 0.127 Inches Maximum
Temp Rating:	550.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	56
Nominal Thread Size:	0.086 Inches
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this self-locking extended washer nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/NAS1291C02M">https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/NAS1291C02M</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.