

P/N NAS1291C3M

Description

Thread: 10-32, self locking, hex, low height, light weight, corrosion resistant steel, NAS1291 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

H42-3

SKU / Model: NAS1291C3M

Minimum Qty (MOQ): 25

NSN: 5310-00-894-3638

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1291C3M Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.330 Inches Maximum
Lubrication:	Dry Film Lubricant
Overall Height:	0.154 Inches Minimum And 0.188 Inches Maximum
Nut Style:	Hexagon
Washer Thickness:	0.015 Inches Minimum
Width Across Flats:	0.243 Inches Minimum And 0.252 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Criticality Code Justification:	Feat
Special Features:	Fluorescent Penetrant Inspect
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Test Data Document:	81349-mil-n-25027 Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1291C3M and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.