

## **P/N NAS1291C8M**

### **Description**

thread: 1/2-20, self locking, hex nut, low height, light weight, corrosion resistant steel, NAS1291 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### 1DAX86A802011

SKU / Model: NAS1291C8M

Minimum Qty (MOQ): 10

NSN: 5310-00-458-2115

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1291C8M Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.814 Inches Maximum
Lubrication:	Dry Film Lubricant
Overall Height:	0.350 Inches Minimum And 0.410 Inches Maximum
Nut Style:	Hexagon
Washer Thickness:	0.040 Inches Minimum
Width Across Flats:	0.556 Inches Minimum And 0.566 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this self-locking extended washer nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/NAS1291C8M">https://military-fasteners.com/nuts/self\_locking+extended+washer+nuts/NAS1291C8M</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.