

Description

Fastener Length: 0-1/1", Thread: 6-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS12970610
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-287-9166
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1297-06-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.332 Inches Minimum And 0.392 Inches Maximum
Fastener Length:	0.987 Inches Minimum And 1.027 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Shoulder Diameter:	0.186 Inches Minimum First Shoulder And 0.189 Inches Maximum First Shoulder
Shoulder Length:	0.635 Inches Minimum First Shoulder And 0.655 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1297 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-06-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.