

**Description**

Fastener Length: 5/8", Thread: 6-32, Thread Length: 11/32", NAS1297 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1297064
Minimum Qty (MOQ):	5
NSN:	5305-00-902-4722
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



\* See page 2 for technical characteristics

## P/N NAS1297-06-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.342 Inches Minimum And 0.402 Inches Maximum
<b>Fastener Length:</b>	0.612 Inches Minimum And 0.652 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.140 Inches Minimum And 0.172 Inches Maximum
<b>Width Between Flats:</b>	0.428 Inches Minimum And 0.440 Inches Maximum
<b>Shoulder Diameter:</b>	0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.250 Inches Minimum First Shoulder And 0.270 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-06-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.