

**Description**

Fastener Length: 5/8", Hole Diameter: 3/64", Thread: 6-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS129706H4
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-541-6213
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1297-06H4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.352 Inches Minimum And 0.400 Inches Maximum
<b>Fastener Length:</b>	0.612 Inches Minimum And 0.652 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.109 Inches Minimum And 0.141 Inches Maximum
<b>Width Between Flats:</b>	0.365 Inches Minimum And 0.377 Inches Maximum
<b>Hole Diameter:</b>	0.046 Inches Minimum And 0.056 Inches Maximum
<b>Internal Drive Style:</b>	W/o Internal Drive
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	32
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Part Name Assigned By Controlling Agency:</b>	Bolt
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Nas-6812 National Std/spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Ams-qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-06H4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.