

Description

Fastener Length: 1", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1297310
Minimum Qty (MOQ):	5
NSN:	5306-00-825-3468
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1297-3-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.362 Inches Minimum
Fastener Length:	0.987 Inches Minimum And 1.027 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Shoulder Diameter:	0.2460 Inches Minimum First Shoulder And 0.2490 Inches Maximum First Shoulder
Shoulder Length:	0.635 Inches Minimum First Shoulder And 0.655 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1297 Professional/industrial Association Standard

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.