

Description

Fastener Length: 1-1/16", Thread: 10-32, Thread Length: 9/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1297311 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-177-5424 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1297-3-11 Specifications

| | |
|----------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.270 Inches Minimum And 0.361 Inches Maximum |
| Fastener Length: | 1.050 Inches Minimum And 1.090 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.140 Inches Minimum And 0.172 Inches Maximum |
| Width Between Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Shoulder Diameter: | 0.2460 Inches Minimum First Shoulder And 0.2490 Inches Maximum First Shoulder |
| Shoulder Length: | 0.698 Inches Minimum First Shoulder And 0.718 Inches Maximum First Shoulder |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-3-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.