

P/N NAS1297-3-14

Military-Fasteners.com

#### Description

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 11/32", NAS1297 series bolt

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1297314
Minimum Qty (MOQ):	10
NSN:	5306-00-143-2299
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS1297-3-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.331 Inches Minimum And 0.391 Inches Maximum
Fastener Length:	1.236 Inches Minimum And 1.276 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Shoulder Diameter:	0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder
Shoulder Length:	0.885 Inches Minimum First Shoulder And 0.905 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this shoulder bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-3-14</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.