

Description

Fastener Length: 1-3/4", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1297322
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-219-7146
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1297-3-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.332 Inches Minimum And 0.392 Inches Maximum
Fastener Length:	1.737 Inches Minimum And 1.777 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Shoulder Diameter:	0.246 Inches Minimum And 0.249 Inches Maximum First Shoulder
Shoulder Length:	1.385 Inches Minimum And 1.405 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1297 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-3-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.