

## Description

Fastener Length: 1-1/1", Thread: 10-32, Thread Length: 9/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1297326                                |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5306-01-033-8140                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1297-3-26 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.270 Inches Minimum And 0.361 Inches Maximum  |
| <b>Fastener Length:</b>                               | 1.987 Inches Minimum And 2.027 Inches Maximum  |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.140 Inches Minimum And 0.172 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.428 Inches Minimum And 0.440 Inches Maximum  |
| <b>Shoulder Diameter:</b>                             | 0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder  |
| <b>Shoulder Length:</b>                               | 1.635 Inches Minimum First Shoulder And 1.655 Inches Maximum First Shoulder  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Shoulder Shape:</b>                                | Round First Shoulder   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall  |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1297 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-3-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.