

P/N NAS1297-3-4

Military-Fasteners.com

### Description

length: 0.622", thread: 10-32, hex head,

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS129734                                 |
|-------------------------|---|
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-00-993-2714                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



# P/N NAS1297-3-4 Specifications

| Thread Class:                                     | За   |  |
|---|--|--|
| Thread Direction:                                 | Right-hand   |  |
| Thread Length:                                    | 0.342 Inches Minimum And 0.392 Inches Maximum  |  |
| Fastener Length:                                  | 0.612 Inches Minimum And 0.652 Inches Maximum  |  |
| Head Style:                                       | Hexagon  |  |
| Head Height:                                      | 0.140 Inches Minimum And 0.172 Inches Maximum  |  |
| Width Between Flats:                              | 0.428 Inches Minimum And 0.440 Inches Maximum  |  |
| Shoulder Diameter:                                | 0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder  |  |
| Shoulder Length:                                  | 0.260 Inches Minimum First Shoulder And 0.270 Inches Maximum First Shoulder  |  |
| Nominal Thread Diameter:                          | 0.190 Inches   |  |
| Thread Quantity Per Inch:                         | 32   |  |
| Minimum Tensile Strength:                         | 125000 Pounds Per Square Inch  |  |
| Hardness Rating:                                  | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |  |
| Shoulder Shape:                                   | Round First Shoulder   |  |
| Material:   | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall<br>Or Steel Comp 4037 Overall  |  |
| Material Document And<br>Classification:          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material<br>Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300<br>Assn Std 6th Material Response Overall |  |
| Surface Treatment:                                | Cadmium Overall And Chromate Overall   |  |
| Surface Treatment Document<br>And Classification: | Qq-s-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall  |  |
| Thread Series Designator:                         | Unjf   |  |
| Specification/standard Data:                      | 80205-nas1297 Professional/industrial Association Standard   |  |
|   |  |  |

# How to Order

Order this shoulder bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-3-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.