

P/N NAS1297-3H6

Description

Fastener Length: 49/64", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12973H6
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-193-4280
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1297-3H6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.311 Inches Minimum And 0.331 Inches Maximum
Fastener Length:	0.737 Inches Minimum And 0.777 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Shoulder Diameter:	0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder
Shoulder Length:	0.385 Inches Minimum First Shoulder And 0.395 Inches Maximum First Shoulder
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1297 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-3H6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.