

**Description**

Fastener Length: 1-15/64", Thread: 1/4-28, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1297412                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-017-6106                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1297-4-12 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.423 Inches Minimum And 0.483 Inches Maximum  |
| <b>Fastener Length:</b>                               | 1.203 Inches Minimum And 1.243 Inches Maximum  |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.172 Inches Minimum And 0.204 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.490 Inches Minimum And 0.502 Inches Maximum  |
| <b>Shoulder Diameter:</b>                             | 0.309 Inches Minimum First Shoulder And 0.312 Inches Maximum First Shoulder  |
| <b>Shoulder Length:</b>                               | 0.760 Inches Minimum First Shoulder And 0.780 Inches Maximum First Shoulder  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Shoulder Shape:</b>                                | Round First Shoulder   |
| <b>Material:</b>                                      | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| <b>Material Document And Classification:</b>          | Mil-b-6812 Mil Spec All Material Responses Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-4-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.