



Military-Fasteners.com

P/N NAS1297-4-4

Description

Fastener Length: 47/64", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS129744
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-488-3826
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1297-4-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.362 Inches Minimum And 0.448 Inches Maximum
Fastener Length:	0.703 Inches Minimum And 0.743 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Shoulder Diameter:	0.3090 Inches Minimum First Shoulder And 0.3120 Inches Maximum First Shoulder
Shoulder Length:	0.260 Inches Minimum First Shoulder And 0.270 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.