

Description

Fastener Length: 1-19/64", Thread: 1/4-28, Thread Length: 7/16", NAS1297 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12974D13
Minimum Qty (MOQ):	5
NSN:	5306-01-482-2241
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1297-4D13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.453 Inches Nominal
Fastener Length:	1.265 Inches Minimum And 1.305 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Shoulder Diameter:	0.309 Inches Minimum First Shoulder And 0.312 Inches Maximum First Shoulder
Shoulder Length:	0.822 Inches Nominal First Shoulder
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.097 Inches Nominal First Hole
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-4D13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.