

P/N NAS1297-4D15

Description

Fastener Length: 1-27/64", Thread: 1/4-28, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS12974D15

Minimum Qty (MOQ): 5

NSN: 5306-01-038-4745

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS1297-4D15 Specifications

3a
Right-hand
0.352 Inches Minimum And 0.448 Inches Maximum
1.391 Inches Minimum And 1.431 Inches Maximum
Hexagon
0.172 Inches Minimum And 0.204 Inches Maximum
0.490 Inches Minimum And 0.502 Inches Maximum
0.309 Inches Minimum First Shoulder And 0.312 Inches Maximum First Shoulder
0.948 Inches Maximum First Shoulder And 0.968 Inches Maximum First Shoulder
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
0.250 Inches
28
125000 Pounds Per Square Inch
26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
1.203 Inches Minimum First Hole And 1.263 Inches Maximum First Hole
Round First Shoulder
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Chromate Overall And Cadmium Overall
Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall
Unjf
80205-nas1297 Professional/industrial Association Standard

How to Order

Order this shoulder bolt from our inventory online by visiting https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-4D15 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.