

Description

Fastener Length: 1-15/32", Thread: 1/4-24, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1297515
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-900-8273
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1297-5-15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.498 Inches Minimum
Fastener Length:	1.436 Inches Minimum And 1.476 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Shoulder Diameter:	0.371 Inches Minimum First Shoulder And 0.374 Inches Maximum First Shoulder
Shoulder Length:	0.948 Inches Minimum First Shoulder And 0.968 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-5-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.