

P/N NAS1297-5-20

Military-Fasteners.com

Description

Fastener Length: 1-25/32", Thread: 1/4-3A, NAS1297 series bolt

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS1297520
Minimum Qty (MOQ):	2
NSN:	5306-01-184-8296
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS1297-5-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.498 Inches Nominal
Fastener Length:	1.748 Inches Minimum And 1.788 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Shoulder Diameter:	0.371 Inches Minimum First Shoulder And 0.374 Inches Maximum First Shoulder
Shoulder Length:	1.260 Inches Minimum First Shoulder And 1.290 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	3a
Minimum Tensile Strength:	6500 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Steel Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Mil-s-6050 Mil Spec Single Material Response Overall Or Mil-s-6098 Mil Spec Single Material Response Overall Or Mil-s-6758 Mil Spec Single Material Response Overall Or Ams 6300 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1297 Professional/industrial Association Standard

How to Order

Order this shoulder bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-5-20</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.