

Description

Fastener Length: 1-3/8", Thread: 1/4-24, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12975D14
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-482-2899
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1297-5D14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.498 Inches Nominal
Fastener Length:	1.383 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Shoulder Diameter:	0.371 Inches Minimum First Shoulder And 0.374 Inches Maximum First Shoulder
Shoulder Length:	0.885 Inches Nominal First Shoulder
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal Overall
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.202 Inches Nominal Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mils-6758 Mil Spec 3rd Material Response Overall Or Ams6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-5D14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.