

Description

Fastener Length: 1-17/32", Thread: 3/8-20, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1297714
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-426-1249
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1297-7-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.629 Inches Nominal
Fastener Length:	1.504 Inches Minimum And 1.544 Inches Maximum
Head Style:	Hexagon
Head Height:	0.265 Inches Minimum And 0.297 Inches Maximum
Width Between Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Shoulder Diameter:	0.495 Inches Minimum First Shoulder And 0.499 Inches Maximum First Shoulder
Shoulder Length:	0.885 Inches Minimum First Shoulder And 0.905 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.437 Inches
Thread Quantity Per Inch:	20
Shoulder Shape:	Round First Shoulder
Material:	Steel Overall
Material Document And Classification:	Mil-b-6812 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-7-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.