

**Description**

Fastener Length: 1-17/32", Thread: 3/8-20, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1297714
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-426-1249
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS1297-7-14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.629 Inches Nominal
<b>Fastener Length:</b>	1.504 Inches Minimum And 1.544 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.265 Inches Minimum And 0.297 Inches Maximum
<b>Width Between Flats:</b>	0.740 Inches Minimum And 0.752 Inches Maximum
<b>Shoulder Diameter:</b>	0.495 Inches Minimum First Shoulder And 0.499 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.885 Inches Minimum First Shoulder And 0.905 Inches Maximum First Shoulder
<b>Nominal Thread Diameter:</b>	0.437 Inches
<b>Thread Quantity Per Inch:</b>	20
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-b-6812 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2, Cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1297-7-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.