

Description

Fastener Length: 33/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS129832
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-436-7216
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1298-3-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.280 Inches Minimum And 0.361 Inches Maximum
Fastener Length:	0.487 Inches Minimum And 0.527 Inches Maximum
Head Style:	Pan
Head Diameter:	0.464 Inches Minimum And 0.493 Inches Maximum
Head Height:	0.133 Inches Minimum And 0.150 Inches Maximum
Shoulder Diameter:	0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder
Shoulder Length:	0.135 Inches Minimum First Shoulder And 0.145 Inches Maximum First Shoulder
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 8630 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1298-3-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.