

**Description**

Fastener Length: 33/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS129832
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-436-7216
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1298-3-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.280 Inches Minimum And 0.361 Inches Maximum
<b>Fastener Length:</b>	0.487 Inches Minimum And 0.527 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.464 Inches Minimum And 0.493 Inches Maximum
<b>Head Height:</b>	0.133 Inches Minimum And 0.150 Inches Maximum
<b>Shoulder Diameter:</b>	0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.135 Inches Minimum First Shoulder And 0.145 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Comp 8630 Overall Or Steel Comp 4037 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1298-3-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.