

Description

Fastener Length: 49/64", Thread: 10-32, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS129836
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-229-8012
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1298-3-6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.342 Inches Minimum And 0.392 Inches Maximum
<b>Fastener Length:</b>	0.737 Inches Minimum And 0.777 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.361 Inches Minimum And 0.385 Inches Maximum
<b>Head Height:</b>	0.103 Inches Minimum And 0.118 Inches Maximum
<b>Shoulder Diameter:</b>	0.246 Inches Minimum And 0.249 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.385 Inches Minimum And 0.395 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-s-7839 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1298 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1298-3-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.