

**Description**

Fastener Length: 53/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS129837                                 |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5305-01-321-4109                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1298-3-7 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.362 Inches Nominal   |
| <b>Fastener Length:</b>                               | 0.810 Inches Minimum And 0.840 Inches Maximum  |
| <b>Head Style:</b>                                    | Pan No. 2  |
| <b>Head Diameter:</b>                                 | 0.464 Inches Minimum And 0.493 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.133 Inches Minimum And 0.150 Inches Maximum  |
| <b>Shoulder Diameter:</b>                             | 0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder                          |
| <b>Shoulder Length:</b>                               | 0.448 Inches Minimum First Shoulder And 0.458 Inches Maximum First Shoulder                          |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch  |
| <b>Shoulder Shape:</b>                                | Round First Shoulder   |
| <b>Material:</b>                                      | Steel Comp 8630 Overall Or Steel Comp 4037 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-6050 Mil Spec 1st Material Response Overall Or Ams 6300 Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1298 Professional/Industrial Association Standard   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1298-3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.