

Description

Screw part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS129838
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-231-3847
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1298-3-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.280 Inches Minimum And 0.361 Inches Maximum
Fastener Length:	0.862 Inches Minimum And 0.902 Inches Maximum
Head Style:	Pan
Head Diameter:	0.464 Inches Minimum And 0.493 Inches Maximum
Head Height:	0.133 Inches Minimum And 0.150 Inches Maximum
Shoulder Diameter:	0.246 Inches Minimum And 0.249 Inches Maximum First Shoulder
Shoulder Length:	0.510 Inches Minimum And 0.520 Inches Maximum First Shoulder
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Mil-s-7839 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1298 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1298-3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.