

**Description**

Screw part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS129838
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-231-3847
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1298-3-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.280 Inches Minimum And 0.361 Inches Maximum
<b>Fastener Length:</b>	0.862 Inches Minimum And 0.902 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.464 Inches Minimum And 0.493 Inches Maximum
<b>Head Height:</b>	0.133 Inches Minimum And 0.150 Inches Maximum
<b>Shoulder Diameter:</b>	0.246 Inches Minimum And 0.249 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.510 Inches Minimum And 0.520 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Mil-s-7839 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1298 Professional/Industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1298-3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.