

## P/N NAS1299-3-11

## **Description**

Fastener Length: 1-5/64", Thread: 10-32, Thread Length: 23/64",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1299311

Minimum Qty (MOQ): 20

NSN: 5305-00-991-6520

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS1299-3-11 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.362 Inches Minimum
Fastener Length:	1.050 Inches Minimum And 1.090 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.491 Inches Minimum And 0.507 Inches Maximum
Shoulder Diameter:	0.246 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder
Shoulder Length:	0.592 Inches Minimum First Shoulder And 0.612 Inches Maximum First Shoulder
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Shoulder Shape:	Round First Shoulder
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1299 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1299-3-11">https://military-fasteners.com/screws/machine+screws/NAS1299-3-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.