



Military-Fasteners.com

P/N NAS1299-3-3

Description

Fastener Length: 37/64", Thread: 10-32, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS129933                                 |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5305-00-461-6934                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1299-3-3 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.342 Inches Minimum And 0.392 Inches Maximum                               |
| <b>Fastener Length:</b>                               | 0.550 Inches Minimum And 0.590 Inches Maximum                               |
| <b>Head Style:</b>                                    | Flat Countersunk  |
| <b>Head Diameter:</b>                                 | 0.447 Inches Minimum And 0.507 Inches Maximum                               |
| <b>Shoulder Diameter:</b>                             | 0.236 Inches Minimum First Shoulder And 0.249 Inches Maximum First Shoulder |
| <b>Shoulder Length:</b>                               | 0.092 Inches Minimum First Shoulder And 0.102 Inches Maximum First Shoulder |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall         |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                              |
| <b>Shoulder Shape:</b>                                | Round First Shoulder  |
| <b>Material:</b>                                      | Steel Comp 8630 Overall Or Steel Comp 4037 Overall                          |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall                 |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1299-3-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.