

## P/N NAS1300-3T10

## **Description**

Fastener Length: 21/32", Thread: 10-32, Thread Length: 21/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS13003T10

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-385-6618

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1300-3T10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.532 Inches Minimum And 0.656 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.656 Inches Maximum
Head Style:	Thumb No. 3
Head Height:	0.453 Inches Minimum And 0.483 Inches Maximum
Width Between Flats:	0.395 Inches Minimum And 0.425 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1300 Professional/industrial Association Standard

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1300-3T10">https://military-fasteners.com/screws/machine+screws/NAS1300-3T10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.