

Description

Fastener Length: 1-", Thread: 10-32, Thread Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS13003T16
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-660-2224
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1300-3T16 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.938 Inches Minimum
Fastener Length:	1.000 Inches Nominal
Head Style:	Thumb No. 3
Head Height:	0.453 Inches Minimum And 0.483 Inches Maximum
Width Between Flats:	0.395 Inches Minimum And 0.425 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1300 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1300-3T16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.