

## P/N NAS1300-3T16

### **Description**

Fastener Length: 1-", Thread: 10-32, Thread Length: 15/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS13003T16

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-660-2224

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1300-3T16 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.938 Inches Minimum
Fastener Length:	1.000 Inches Nominal
Head Style:	Thumb No. 3
Head Height:	0.453 Inches Minimum And 0.483 Inches Maximum
Width Between Flats:	0.395 Inches Minimum And 0.425 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1300 Professional/industrial Association Standard

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1300-3T16">https://military-fasteners.com/screws/machine+screws/NAS1300-3T16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.