



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS1301C10-6**

## Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1301C106                               |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5305-01-320-8838                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N NAS1301C10-6 Specifications

|  |  |
|--|--|
| Thread Class:                                    | 2a   |
| Thread Direction:                                | Right-hand   |
| Thread Length:                                   | 0.203 Inches Nominal   |
| Fastener Length:                                 | 0.343 Inches Minimum And 0.375 Inches Maximum  |
| Head Style:                                      | Pan No. 2  |
| Head Diameter:                                   | 0.357 Inches Minimum And 0.373 Inches Maximum  |
| Head Height:                                     | 0.338 Inches Minimum And 0.348 Inches Maximum  |
| Washer Quantity:                                 | 2  |
| Internal Drive Style:                            | Cross Recess Type 1  |
| Nominal Thread Diameter:                         | 0.190 Inches   |
| Thread Quantity Per Inch:                        | 32   |
| Secondary Washer Relationship To Primary Washer: | Not Identical  |
| Secondary Washer Style:                          | Flat   |
| Primary Washer Outside Diameter:                 | 0.334 Inches Nominal   |
| Secondary Washer Outside Diameter:               | 0.338 Inches Minimum And 0.348 Inches Maximum  |
| Primary Washer Style:                            | Split Helical Ring   |
| Primary Washer Material Thickness:               | 0.029 Inches Minimum And 0.035 Inches Maximum  |
| Secondary Washer Material Thickness:             | 0.029 Inches Minimum And 0.035 Inches Maximum  |
| Material:  | Steel Comp 304 Fastener Or Steel Comp 302 Fastener   |
| Material:  | Steel Comp 302 Primary Washer Or Steel Comp 301 Primary Washer Or Steel Comp 304 Primary Washer Or Steel Comp 316 Primary Washer |
| Material:  | Steel Comp 321 Secondary Washer Or Steel Comp 347 Secondary Washer Or Steel Comp 348 Secondary Washer                            |
| Material Document And Classification:            | Mil-s-6721 Mil Spec All Material Responses Secondary Washer Or Mil-s-5059 Mil Spec All Material Responses Secondary Washer       |
| Material Document And Classification:            | Qq-s-763 Cl 4 Fed Spec All Material Responses Fastener Or Mil-s-7720 Mil Spec 1st Material Response Fastener                     |
| Thread Series Designator:                        | Unf  |
| Specification/standard Data:                     | 80205-nas1301 Professional/industrial Association Standard   |

## How to Order

Order this assembled washer screw from our inventory online by visiting <https://military-fasteners.com/screws/assembled+washer+screws/NAS1301C10-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.