

P/N NAS1301C10-6

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 3/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1301C106

Minimum Qty (MOQ): 10

NSN: 5305-01-320-8838

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1301C10-6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.203 Inches Nominal
Fastener Length:	0.343 Inches Minimum And 0.375 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.338 Inches Minimum And 0.348 Inches Maximum
Washer Quantity:	2
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Secondary Washer Relationship To Primary Washer:	Not Identical
Secondary Washer Style:	Flat
Primary Washer Outside Diameter:	0.334 Inches Nominal
Secondary Washer Outside Diameter:	0.338 Inches Minimum And 0.348 Inches Maximum
Primary Washer Style:	Split Helical Ring
Primary Washer Material Thickness:	0.029 Inches Minimum And 0.035 Inches Maximum
Secondary Washer Material Thickness:	0.029 Inches Minimum And 0.035 Inches Maximum
Material:	Steel Comp 304 Fastener Or Steel Comp 302 Fastener
Material:	Steel Comp 302 Primary Washer Or Steel Comp 301 Primary Washer Or Steel Comp 304 Primary Washer Or Steel Comp 316 Primary Washer
Material:	Steel Comp 321 Secondary Washer Or Steel Comp 347 Secondary Washer Or Steel Comp 348 Secondary Washer
Material Document And Classification:	Mil-s-6721 Mil Spec All Material Responses Secondary Washer Or Mil-s-5059 Mil Spec All Material Responses Secondary Washer
Material Document And Classification:	Qq-s-763 Cl 4 Fed Spec All Material Responses Fastener Or Mil-s-7720 Mil Spec 1st Material Response Fastener
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1301 Professional/industrial Association Standard

How to Order

